



Gear Type / Pneumatic Variable Speed Auto Drilling Machine

KSA-16A



KSA-16B



KSA-25A



KSA-25B



KSD-32



KST-670





SPECIFICATIONS:

TYPE	KSA- 16A	KSA- 16B	KSA- 25A	KSA- 25B	KSD- 32	KST- 670	
Dia. of spindle(mm)	Dia. 65	Dia. 65	Dia. 95	Dia. 95	Dia. 95	Dia. 95	
Taper of spindle	MT 2#	MT 2#	MT 3#	MT 3#	MT 3#	MT 3#	
Step of spindle(mm)	4	4	6	6	9	9	
Spindle stroke(mm)	100	100	140	140	140	140	
Spindle to column(mm)	175	175	230	230	230	230	
Spindle to disc(mm)	420	420	630	630	630	630	
Spindle to base(mm)	620	620	930	930	930	930	
Drilling capability(mm)	4-16	4-16	8-25	8-25	8-32	Drilling:8-32 Tapping:8-23	
Cover size (LxWxH)	608x214x125	608x214x125	725x262x157	725x262x157	725x262x157	725x262x157	
Dia. of column(mm)	80	80	102	102	102	102	
Dia. of disc(mm)	320	320	420	420	420	420	
Base size(LxW)	500x300	500x300	615x385	615x385	615x385	615x385	
Speed	50Hz	480-1980	480-1980	200-1600	200-1600	120-1390	120-1390
	60Hz	560-2100	560-2100	210-1700	210-1700	135-1570	135-1570
Motor	1HP- 4P	1HP- 4P	2HP- 6P	2HP- 6P	2HP- 6P	2HP- 6P	
Machine size(LxWxH)	650x410x1090	650x410x1090	810x450x1090	810x450x1545	810x420x1545	810x420x1545	
Machine weight(kg)	105	105	210	210	200	205	