

HORIZONTAL BAND SAWS

SH-6550



SH-360C






SH-7550S



SH-300



Specification

Model		SH-300	SH-360E	SH-6550	SH-7550S
Max. Capacity		300 mm (12")	360 mm (14")	500 mm (19.7")	500 mm (20")
		300 x 300 mm (12" x 12")	360 x 360 mm (14" x 14")	500 x 500 mm (19.7" x 19.7")	500 x 500 mm (20" x 20")
	 (H x W)	300 x 400 mm (12" x 15.7" option: 300 x 355 mm (12" x 14")	360 x 420 mm (14" x 16.5")	500 x 650 mm (19.7" x 25.6")	500 x 750 mm (20" x 30")
Blade	Capacity	3820L x 27W x 0.9T mm (150" x 1.06" x 0.035") option: 3660L x 27W x 0.9T mm	4115L x 34W x 1.1T mm (162" x 1.33" x 0.043")	5815L x 54W x 1.3T mm (229" x 2.1" x 0.05")	6040L x 54W x 1.3T (238" x 2.1" x 0.05")
	Speed	21,38,55,68,81 m/min (60HZ) (70,127,180,224,267 fpm)	27,40,54,68,80 m/min (60HZ) (89,132,178,224,264 fpm)	20 - 100 m/min (66 - 328 fpm)	20 - 100 m/min (66 - 328 fpm)
	Tension	Spring loaded		Hydraulic (with blade breakage detection)	
Motor	Blade	2.22 kw (3 HP)	3.7 kw (5 HP)	5.6 kw (7.5 HP)	5.6 kw (7.5 HP)
	Hydraulic	0.18 kw (1/4 HP)	0.18 kw (1/8 HP)	0.75 kw (1 HP)	1.5 kw (2 HP)
	Coolant	0.1 kw (1/8 HP)	0.1 kw (1/8 HP)	0.18 kw (1/4 HP)	0.18 kw (1/4 HP)
Tank	Hydraulic	25 L (6.2 gal)	25 L (6.2 gal)	40 L (10 gal)	40 L (10 gal)
	Coolant	60 L (15 gal)	60 L (15 gal)	85 L (21.25 gal)	85 L (21.25 gal)
Work Bed Height		660 mm (26")	665 mm (26")	700 mm (27.6")	700 mm (27.6")
Net Weight		700 kgs (1540 lbs)	800 kgs (1760 lbs)	1700 kgs (3740 lbs)	1900 kgs (4180 lbs)
Gross Weight		800 kgs (1760 lbs)	900 kgs (1980 lbs)	1900 kgs (4180 lbs)	2100 kgs (4620 lbs)
Floor Space (L x W x H)		1905 x 800 x 1700 mm (75" x 31.5" x 67")	2286 x 1194 x 1600 mm (90" x 47" x 63")	3030 x 1410 x 2010 mm (119" x 55.5" x 79")	3150 x 1410 x 2010 mm (124" x 55.5" x 79")
Shipping Space (L x W x H)		2185 x 900 x 1728 mm (86" x 35.4" x 68")	2386 x 1300 x 1700 mm (94" x 50.5" x 67")	3105 x 1450 x 2210 mm (122" x 57" x 87")	3225 x 1450 x 2210 mm (127" x 57" x 87")