


SK SERIES

CNC DOUBLE COLUMN MACHINING CENTER CROSSRAIL MOVABLE TYPE





SPECIFICATION

CONTENTS	UNIT	SK-1500	SK- 2000	SK- 2500	SK- 3000
Working length	mm	2000~6000	2500~6000	3000~6000	4000~6000
Working width	mm	1500	2000	2500	3000
Crossrail height	mm	1000	1200	1500	1700
Spindle feeding	mm	750	750	750	750
Table size	mm	1200 x 1500	1600x 2500	2000x 3000	2500x 4000
Spindle's speed	rpm	L / 30~ H / 3000 (stepless)			
Spindle's power	kw	Continuous 18.5kw, 30minute: 22KW			
ATC	pc	24			
Numerical control system	FANUC-MITSUBISHI - SIEMENS				
* special specification can be made separately.					

Special Accessory

- 1.Side milling head.
- 2.Numerical control system.
- 3.90 ° angle milling head.
- 4.90 ° angle milling head's lifting table.
- 5.Coolant through spindle.
- 6.ATC 32 - 40 pcs.
- 7.Spindle power 18.5W
(Continuous 18.5KW, 30minutes:22KW)
- 6.Digital readout.
- 7.Fully closed safety guard.