



# KP - 200,225,280,320,380,450

## Hydraulic Power Hack Saws



# KB - 30,36,45

## Vertical Metal Cutting Band Saws



**Combittech**

Taiwan Combittech Co.,Ltd.  
160 Huei-Chung Road Taichung 407 Taiwan

Tel:+886 4-2311 2413 Fax:+886 4-2311 2415  
<http://www.combittech.com.tw>  
e-mail:info@combittech.com.tw



## KP SPECIFICATIONS:

Models		Unit	KP- 200	KP- 225	KP- 280	KP- 320	KP- 380	KP- 450
Cutting capacity	Round	mm(in)	200(7 7/8)	225(8 7/8)	280(11)	320(12 5/8)	380(15)	450(17 7/10)
	Square HxW	mm (in)	190x190 (7 3/16x 7 3/16)	230x 220 (9x 8 13/16)	280x 250 (11x 9 13/16)	300x300 (11 3/4x 11 3/4)	330x350 (13x 13 3/4)	400x430 (15 3/4x 17)
Max. Cutting Degree		mm	45°/ 90	45°/ 120	45°/ 130	45°/ 140	45°/ 150	45°/ 160
Distance of Strokes		mm(in)	120(4 21/64)	140(5 1/2)	140(5 1/2)	140(5 1/2)	140(5 1/2)	160(6 3/10)
Strokes per min			105,125	80, 100, 120				
Blade Size		mm(in)	350x32x1.6x8.3 (14x1 1/4x 1/16x 11/32)	400x32x1.6x8.3 (16x1 1/4x1/16x11/32)	450x32x1.6x8.3 (18x1 1/4x1/16x11/32)	500x38x2x10.3 (20x1 1/2x1/13x13/32)	550x 45x 2.25x10.3 (22x1 3/4x 1/12x 13/32)	650x50x2.5x12.3 (26x2x1/10x1/2)
Main motor		HP(KW)	4P,1HP(0.75)	4P,2HP(1.5)	4P,2HP(1.5)	4P,2HP(1.5)	4P,2HP(1.5)	4P,3HP(2.2)
Measurement (LxWxH)		mm (in)	1240x 730 x 1010 (48 13/16x 28 11/16x 39 11/16)	1400x 850x 1100 (48 1/8x 33 7/16x 43 5/16)	1470x850x1100 (57 1/8x33 7/16x 43 5/16)	1550x850x1200 (61x33 1/4x47 5/16)	1550x850x1200 (61x33 1/4x47 5/16)	1970x940x1520 (77 3/5x37x59 21/2)
Weight Net/Gross		kgs (lbs)	270/ 330 (594/ 726)	485/ 545 (1067/ 1199)	520/580 (1144/1276)	600/660 (1320/1450)	645/705 (1419/1551)	800/880 (1760/1936)

## KB SPECIFICATIONS:

Models		Unit	KB - 30	KB - 36	KB - 45
Cutting capacity	throat depth	mm(in)	310(12 3/8)	355(14)	455(17 15/16)
	max, work height	mm(in)	175(6 7/8)	230(9 1/16)	255(10 1/16)
Table size		mm(in)	500x400(19 1/2x15 1/4)	500x400(19 1/2x15 1/4)	600x500(23 1/2x19 1/2)
Table inclination (4 ways)			15°	15°	15°
Saw blade length		mm(in)	2520(99 1/4)	2840(111 13/16)	3490(137 3/8)
Saw blade width		mm	3-16	3-16	3-16
Saw blade speeds		m/min(fpm)	20-90 (65-295)	20-90 (65-295)	25-115(85-375)
Butt welder capacity		mm(in)	2.4KVA, 3-16mm(1/8-5/8)	2.4KVA, 3-16mm(1/8-5/8)	2.4KVA, 3-16mm(1/8-5/8)
Drive motor		HP(KW)	1/2HP(0.4)	1HP(0.75)	1HP(0.75)
Net Weight (approx.)		kgs(lbs)	225(496)	250(551)	300(660)
Gross weight (approx.)		kgs(lbs)	285(628)	310(683)	370(814)
Measurement (LxWxH)		mm(in)	920x550x1680 (36 3/16x21 11/16x 66 3/16)	940x560x1850 (37 3/16x22x72 13/16)	1110x660x2020 (43 11/16x26x79 1/4)